

MANITOU MC 25-4 ST5

FORKLIFT CO FLEET / FLT34 / OPEN CANOPY



Representative Manitou model image

CAPACITY AT A GLANCE

2,500 kg

maximum rated capacity @ 500 mm load centre

1,988 mm

FLT34 mast lowered height (h1)

2,500

NOMINAL CAPACITY
kg at 500 mm load centre

1,988

MAST LOWERED
mm - FLT34

1,450

OVERALL WIDTH
mm across vehicle

OPEN

OPERATOR AREA
canopy / no enclosed cab

FITTED FLT34 MAST

Fitted mast	FLT34 - free lift triplex
Mast lowered height (h1)	1,988 mm
Maximum rated capacity	2,500 kg
Load centre	500 mm
Lift height (h3)	3,400 mm
Free lift (h2)	1,210 mm
Extended mast (h4)	4,236 mm

DIMENSIONS

Length to fork face	3,045 mm
Overall width	1,450 mm
Wheelbase	1,900 mm
Forks - T x W x L	40 x 100 x 1,200 mm
Ground clearance - centre	310 mm
Travel clearance	Measure highest fitted point

TRUCK SPECIFICATION

Model	MC 25-4 ST5
Power source	Diesel
Drive wheels	4
Tyre type	Pneumatic
Engine	Kubota D1803 CRT E5B
Engine power	37 kW

PERFORMANCE / CONFIGURATION

Travel - laden / unladen	12 / 24.50 km/h
Lift - laden / unladen	0.47 / 0.46 m/s
Lower - laden / unladen	0.50 / 0.30 m/s
Hydraulic flow	42 L/min
Hydraulic pressure	200 bar
Capacity at full lift*	1,900 kg / 1,800 kg SS
Transport weight	Confirm fitted unit weight



CAPACITY AND CONFIGURATION NOTE

1,988 mm is mast height, not overall clearance. Check guard, beacon and attachments. *Manufacturer FLT34 figures: without / with hooked-on sideshift (SS). Fitted load plate governs. Issued 22 September 2026.

Source: supplied Manitou technical sheet. Fitted data plate and applicable load chart govern capacity.

1 / 1