

MANITOU MC-X 18-4

FORKLIFT CO FLEET / FLT34 / OPEN CANOPY



Representative Manitou model image

CAPACITY AT A GLANCE

1,800 kg

maximum rated capacity @ 500 mm load centre

1,988 mm

FLT34 mast lowered height (h1)

1,800

NOMINAL CAPACITY

kg at 500 mm load centre

1,988

MAST LOWERED

mm - FLT34

1,450

OVERALL WIDTH

mm across vehicle

OPEN

OPERATOR AREA

canopy / no enclosed cab

FITTED FLT34 MAST

Fitted mast	FLT34 - free lift triplex
Mast lowered height (h1)	1,988 mm
Maximum rated capacity	1,800 kg
Load centre	500 mm
Lift / free lift / capacity	Refer to fitted data plate
Mast configuration source	Forklift Co confirmation

TRUCK SPECIFICATION

Model	MC-X 18-4
Power source	Diesel
Drive wheels	4
Tyre type	Pneumatic
Engine	Kubota V1505
Engine power	27 kW

DIMENSIONS

Length to fork face	2,950 mm
Overall width	1,450 mm
Wheelbase	1,900 mm
Forks - T x W x L	35 x 100 x 1,150 mm
Ground clearance - centre	310 mm
Travel clearance	Measure highest fitted point

PERFORMANCE / CONFIGURATION

Travel - laden / unladen	12 / 24.90 km/h
Lift - laden / unladen	0.40 / 0.40 m/s
Lower - laden / unladen	0.40 / 0.40 m/s
Hydraulic flow	37 L/min
Hydraulic pressure	180 bar
Transport weight	Confirm fitted unit weight



CAPACITY AND CONFIGURATION NOTE

1,988 mm is mast height, not overall clearance. Check guard, beacon and attachments. FLT34 and lowered height confirmed by Forklift Co; supplied MC18 sheet does not list this mast. Issued 22 September 2026.

Source: supplied Manitou technical sheet. Fitted data plate and applicable load chart govern capacity.

1 / 1